

IN THE SPECIFICATION

Please replace the paragraph beginning at page 4, line 26 (as numbered) with:

~~An exemplary~~ Exemplary embodiments of the invention will below be elucidated by way of example on the basis of the figures.

Please replace the paragraph beginning at page 5, line 26 (as numbered) with:

The pairs of wall elements 10a, 10b connected to each other have respective ends 11a, 11b with respective recesses 12a, 12b arranged in there. The innermost legs 32a, 32b fit into the recesses 12a, 12b. The ends 11a, 11b have respective head surfaces 13a, 13b which abut each other in the connection assembly 1. The recesses 12a, 12b, the innermost legs 32a, 32b and the inclined head surfaces 13a, 13b form connection means to ~~connect~~ couple the wall elements 10a, 10b and the coupling profile 30 one to the other. In general the angles β and γ will be of equal size here, and equal to $\alpha/2$, in which the angles β and γ are the angles with which the respective head surfaces 13, 13b have been bevelled as indicated in figure 1B, and in which the angle α is the angle forming the coupling profile 30 on the side of the wall elements 10a, 10b to be connected. The angles β and γ are the respective angles the inclined head surfaces 13a, 13b make with the respective surfaces that are perpendicular to the longitudinal direction of the respective wall elements 10a, 10b.

Please replace the paragraph beginning at page 7, line 14 (as numbered) with:

As has been described with figures 1A and 1B, the pairs of wall elements 10a, 10b 20a, 20b (figures 3A, 3B) are ~~connected to~~ coupled by the coupling profile 30. Also the lower edge members 50a, 50b are ~~connected~~ coupled in a similar way ~~to~~ by the coupling profile 30. Moreover the pairs of wall elements 10a, 10b and 20a, 20b are also connected one to the other by means of upright edges 14a, 14b and recesses 25a, 25b cooperating with them, and the lowermost pair of wall elements 10a, 10b is connected to lower edge members 50a, 50b by means of cooperating recesses 15a, 15b, respectively, and edges 55a, 55b cooperating with them.

Please replace the paragraph beginning at page 8, line 4 (as numbered) with:

Therefore, the coupling profile connection-assembly according to the invention ~~can to~~ offers a clamp-fixed, i.e., interengagement or confinement connection without glue or fastener herein called coupling for both the ~~pairs of~~ wall elements 10a, 10b, 20a, 20b and lower edge members 50a, 50b as well as the cover profile 40. The cover profile 40 and the pairs of wall elements 10a, 10b, 20a, 20b can be made of the same kind of wood because the cover profile 40 has no load-bearing function.